

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. A processing unit, comprising:  
a plurality of subcircuits;  
5       circuitry for generating a clock signal to said  
plurality of subcircuits;  
      circuitry for detecting the assertion of a control  
signal; and  
      circuitry coupled to said detecting circuitry for  
10       disabling the clock signal to ones of said subcircuits  
      responsive to said control signal.
2. The processing unit of Claim 1 wherein said  
disabling circuitry comprises circuitry for maintaining  
15       the clock signal to said ones of said subcircuits in a  
      predetermined state.
3. The processing unit of Claim 1 and further  
comprising circuitry for generating an acknowledge signal  
20       indicating that the clock signal to said ones of said  
      subcircuits has been disabled.
4. The processing unit of Claim 1 wherein said  
disabling circuitry comprises circuitry for executing  
25       instructions currently in one or more of said subcircuits  
      prior to disabling said ones of said subcircuits.
5. The processing unit of Claim 4 wherein said one  
or more subcircuits comprise a microcode memory and an  
30       execution unit.
6. The processing unit of Claim 1 and further  
comprising circuitry for resuming the clock signal to  
said ones of said subcircuits responsive to de-assertion  
35       of said control signal.

7. The processing unit of Claim 1 and further comprising circuitry for generating an interrupt responsive to detecting assertion of said control signal.

8. The processing unit of Claim 7 and further comprising an exception processor for executing a microcode routine responsive to said interrupt.

9. A computer comprising:  
a processing unit comprising:  
a plurality of subcircuits;  
circuitry for generating a clock signal to said plurality of subcircuits;  
circuitry for detecting the assertion of a control signal; and  
circuitry coupled to said detecting circuitry for disabling the clock signal to ones of said subcircuits responsive to said control signal;  
circuitry for detecting conditions for suspending operations of said processing unit and asserting said control signal responsive thereto; and  
circuitry for detecting conditions for resuming operation of said processing unit and de-asserting said control signal responsive thereto.

10. The computer of Claim 9 and further comprising a display for outputting data.

11. The computer of Claim 10 and further comprising circuitry for disabling said display.

12. The computer of Claim 10 and further comprising a coprocessor coupled to said processing unit.

13. The computer of Claim 9 wherein said disabling circuitry comprises circuitry for disabling the clock signals to said ones of said subcircuits after said  
5 executing instructions in one or more of said subcircuits.

14. The computer of Claim 9 wherein said processing unit further comprises circuitry for resuming the clock signal to said ones of said subcircuits  
10 responsive to de-assertion of said control signal.

15. The computer of Claim 9 wherein said processing unit further comprises circuitry for generating an acknowledge signal indicating that the clock signal to said ones of said subcircuits has been disabled.  
15

16. A method of conserving power consumed by a processing unit comprising the steps of:  
20 generating a clock signal to a plurality of subcircuits;

detecting the assertion of a control signal;  
disabling the clock signal to ones of said subcircuits responsive to said control signal.  
25

17. The method of Claim 16 wherein said disabling step comprises the step of maintaining the clock signal to said ones of said circuits in a predetermined state.

18. The method of Claim 16 and further comprising the step of generating an acknowledge signal indicating that the clock signal to said ones of said subcircuits has been disabled.  
30

19. The method of Claim 16 wherein said disabling step comprises disabling the clock signal to said ones of said subcircuits after said executing instructions in ones of said subcircuits.

20. The method of Claim 16 and further comprising the step of resuming the clock signal to said ones of said subcircuits responsive to de-assertion of said control signal.

21. The method of Claim 16 and further comprising the steps of generating an interrupt responsive to detecting said control signal.

22. The method of Claim 21 and further comprising the step of executing a microcode routine responsive to said interrupt.